

STANDARDS THAT MAKE THE *DIFFERENCE*



Tilt-n-Lock

For Viwinco Brand Windows

EDGEMONT STANDARD REPLACEMENT WINDOW

Standard Features vs. Most Competition

- **Double-Strength Glass** → No Up-Charge
- **Low-E/Argon Gas** → No Up-Charge
- **1-1/8"** Replaceable Sill Dam Mortised In To The Jamb
- **.0765 Sill Profile** Thickness → More Vinyl
- **High Performance Spacer**
- **5 Degree True Sloped Sill**
- **Trimmable Leg Flange**
- **DP35**
- **Available Within 1 Week**
- **Extruded Screen is Standard**
- Available in **White** or **Tan** Solid Extrusions
- Available as a **Double-Hung, 2- and 3-Lite Slider, Picture, and Hopper**

CAMBRIDGE PREMIUM REPLACEMENT WINDOW

- **Tilt-n-Lock**
- **Lifetime Glass Breakage Warranty** (on -hung windows only)
- **15/16"** Glass Unit Thickness
- **1-3/8"** Replaceable Sill Dam Mortised In To The Jamb
- **.080 Sill Profile** Thickness → 5-6 Lbs. More Vinyl
- **3/4"** Stainless Steel Sash Balance
- **Triple** Weather Stripped
- **Heavy Duty** Tilt Pins
- **DP55**
- **Available Within 1 Week**
- **Extruded Half-Screens are Standard, w/Locking Half Screen** Available as an **Upgrade**
- Available in **White, Tan and Clay** Solid Extrusions
- Available in **Midnight Black or Bronze** Exterior Laminate
- Available as a **Single- and Double-Hung, Casement, 2- and 3-Lite Slider, Geometric, Picture, Bay/Bow & Mulled Units**



www.Viwinco.com